A CHARACTERIZATION OF THE RIVLIN-ERICKSEN VISCOELASTIC FLUID IN THE PRESENCE OF ROTATION

Ajaib S. Banyal

Department of Mathematics, Govt. College Nadaun (Hamirpur), (HP) INDIA 177033 *Author for Correspondence

ABSTRACT

A layer of Rivlin-Ericksen viscoelastic fluid heated from below is considered in the presence of uniform vertical rotation. Following the linearized stability theory and normal mode analysis, the paper mathematically established the condition for characterizing the oscillatory motions which may be neutral or unstable, for rigid boundaries at the top and bottom of the fluid. It is established that all non-decaying slow motions starting from rest, in a Rivlin-Ericksen viscoelastic fluid of infinite horizontal extension and finite vertical depth, which is acted upon by uniform vertical rotation, opposite to gravity and a constant vertical adverse temperature gradient, are necessarily non-oscillatory, in the regime

$$\frac{T_A(1+\pi^2 F)}{\pi^4} \le 1,$$

where T_A is the Taylor number and F is the viscoelasticity parameter. The result is important since it hold for all wave numbers and for horizontal rigid boundaries of infinite extension at the top and bottom of the fluid, and the exact solutions of the problem investigated in closed form, is not obtainable.

Key Words: Thermal Convection, Rivlin-Ericksen Fluid, Rotatio, Pes, Rayleigh Number, Taylor Number

INTRODUCTION

Stability of a dynamical system is closest to real life, in the sense that realization of a dynamical system depends upon its stability. Right from the conceptualizations of turbulence, instability of fluid flows is being regarded at its root. The thermal instability of a fluid layer with maintained adverse temperature gradient by heating the underside plays an important role in Geophysics, interiors of the Earth, Oceanography and Atmospheric Physics, and has been investigated by several authors Bénard, (1900); Rayleigh, (1916); Jeffrey, (1926). under different conditions. A detailed account of the theoretical and experimental study of the onset of Bénard Convection in Newtonian fluids, under varying assumptions of hydrodynamics and hydromagnetics, has been given by Chandrasekhar, (1981). The use of Boussinesq approximation has been made throughout, which states that the density changes are disregarded in all other terms in the equation of motion except the external force term. Bhatia and Steiner, (1972) have considered the effect of uniform rotation on the thermal instability of a viscoelastic (Maxwell) fluid and found that rotation has a destabilizing influence in contrast to the stabilizing effect on Newtonian fluid. The thermal instability of a Maxwell fluid in hydromagnetics has been studied by Bhatia and Steiner, 1973). They have found that the magnetic field stabilizes a viscoelastic (Maxwell) fluid just as the Newtonian fluid. Sharma, (1976) has studied the thermal instability of a layer of viscoelastic (Oldroydian) fluid acted upon by a uniform rotation and found that rotation has destabilizing as well as stabilizing effects under certain conditions in contrast to that of a Maxwell fluid where it has a destabilizing effect. In another study Sharma, (1975) has studied the stability of a layer of an electrically conducting Oldroyd fluid, (1958) in the presence of magnetic field and has found that the magnetic field has a stabilizing influence.

There are many elastic-viscous fluids that cannot be characterized by Maxwell's constitutive relations or Oldroyd's, (1958) constitutive relations. Two such classes of fluids are Rivlin-Ericksen's and Walter's (model B') fluids. Rivlin-Ericksen, (1955) have proposed a theoretical model for such one class of elastic-viscous fluids. Sharma and kumar, (1996) have studied the effect of rotation on thermal instability

Research Article

in Rivlin-Ericksen elastico-viscous fluid and found that rotation has a stabilizing effect and introduces oscillatory modes in the system. Kumar *et al.*, (2006) considered effect of rotation and magnetic field on Rivlin-Ericksen elastico-viscous fluid an found that rotation has stabilizing effect, where as magnetic field has both stabilizing and destabilizing effects. A layer of such fluid heated from below or under the action of magnetic field or rotation or both may find applications in geophysics, interior of the Earth, Oceanography, and the atmospheric physics.

Pellow and Southwell, (1940) proved the validity of PES for the classical Rayleigh-Bénard convection problem. Banerjee *et al.*, (1981) gave a new scheme for combining the governing equations of thermohaline convection, which is shown to lead to the bounds for the complex growth rate of the arbitrary oscillatory perturbations, neutral or unstable for all combinations of dynamically rigid or free boundaries and, Banerjee and Banerjee, (1984) established a criterion on characterization of non-oscillatory motions in hydrodynamics which was further extended by Gupta *et al.*,(1986). However no such result existed for non-Newtonian fluid configurations, in general and for Rivlin-Ericksen viscoelastic fluid configurations, in particular. Banyal, (2011) have characterized the non-oscillatory motions in couple-stress fluid.

Keeping in mind the importance of Rivlin-Ericksen viscoelastic fluids, as stated above, this article attempts to study Rivlin-Ericksen viscoelastic fluid heated from below in the presence of uniform vertical rotation, with rigid boundaries and it has been established that the onset of instability in a Rivlin-Ericksen viscoelastic fluid heated from below, in the presence of uniform vertical rotation, cannot manifest itself as oscillatory motions of growing amplitude if the Taylor number T_A and the viscoelasticity parameter F,

satisfy the inequality, $\frac{T_A(1+\pi^2 F)}{\pi^4} \le 1$, for all wave numbers and for horizontal rigid boundaries of

infinite extension at the top and bottom of the fluid.

FORMULATION OF THE PROBLEM AND PERTURBATION EQUATIONS

Considered an infinite, horizontal, incompressible electrically conducting Rivlin-Ericksen viscoelastic fluid layer, of thickness d, heated from below so that, the temperature and density at the bottom surface z = 0 are T_0 and ρ_0 and at the upper surface z = d are T_d and ρ_d respectively, and that a uniform adverse

temperature gradient $\beta \left(= \left| \frac{dT}{dz} \right| \right)$ is maintained. The fluid is acted upon by a uniform vertical

rotation $\vec{\Omega}(0,0,\Omega)$, parallel to the force field of gravity $\vec{g}(0,0,-g)$.

The equation of motion, continuity and heat conduction, governing the flow of Rivlin-Ericksen viscoelastic fluid in the presence of rotation (Rivlin and Ericksen (1955); Chandrasekhar (1981) and Kumar et al (2006) are:

$$\frac{\partial \vec{q}}{\partial t} + \left(\vec{q}.\nabla\right)\vec{q} = -\nabla\left(\frac{p}{\rho_o} - \frac{1}{2}\left|\vec{\Omega}\times\vec{r}\right|^2\right) + \vec{g}\left(1 + \frac{\delta\rho}{\rho_0}\right) + \left(v + v\cdot\frac{\partial}{\partial t}\right)\nabla^2\vec{q} + 2\left(\vec{q}\times\vec{\Omega}\right), \quad (1)$$

$$\nabla \cdot \vec{q} = 0, \quad (2)$$

$$\frac{\partial T}{\partial t} + (\vec{q}.\nabla)T = \kappa\nabla^2 T, \quad (3)$$

Where ρ , p, T, v, v and q(u, v, w) denote respectively the density, pressure, temperature, kinematic

viscosity, kinematic viscoelasticity and velocity of the fluid, respectively and r(x, y, z).

The equation of state for the fluid is

$$\rho = \rho_0 \left[1 - \alpha \left(T - T_0 \right) \right], \tag{4}$$

Where the suffix zero refer to the values at the reference level z = 0. Here g(0,0,-g) is acceleration due to gravity and α is the coefficient of thermal expansion. In writing the equation (1), we made use of the Boussinesq approximation, which states that the density variations are ignored in all terms in the equation of motion except the external force term. The thermal diffusivity κ is assumed to be constant.

The initial state is one in which the velocity, density, pressure, and temperature at any point in the fluid are, respectively, given by

$$\vec{q} = (0,0,0)$$
, $\rho = \rho(z)$, $p = p(z)$, $T = T(z)$, (5)

Assume small perturbations around the basic solution and let $\delta \rho$, δp , θ , and q(u, v, w) denote respectively the perturbations in density ρ , pressure p, temperature T and velocity $\vec{q}(0,0,0)$. The change in density $\delta \rho$, caused mainly by the perturbation θ in temperature, is given by

$$\rho + \delta\rho = \rho_0 [1 - \alpha (T + \theta - T_0)] = \rho - \alpha \rho_0 \theta, \text{ i.e. } \delta\rho = -\alpha \rho_0 \theta.$$
(6)
Then the linearized perturbation equations are

$$\frac{\partial q}{\partial t} = -\frac{1}{\rho_0} \nabla \delta p - \vec{g} \,\alpha \theta + \left(v + v \,\frac{\partial}{\partial t} \right) \nabla^2 \vec{q} + 2 \left(\vec{q} \times \vec{\Omega} \right), \tag{7}$$

$$\nabla \cdot q = 0, \tag{8}$$

$$\frac{\partial\theta}{\partial t} = \beta w + \kappa \nabla^2 \theta, \qquad (9)$$

Within the framework of Boussinesq approximation, equations (6) - (9), become

$$\frac{\partial}{\partial t}\nabla^2 w = \left(v + v'\frac{\partial}{\partial t}\right)\nabla^4 w + g\alpha \left(\frac{\partial^2 \theta}{\partial x^2} + \frac{\partial^2 \theta}{\partial y^2}\right) - 2\Omega \frac{\partial \zeta}{\partial z},$$
(10)

$$\frac{\partial \varsigma}{\partial t} = \left(v + v' \frac{\partial}{\partial t} \right) \nabla^2 \varsigma + 2\Omega \frac{\partial w}{\partial z}, \tag{11}$$

$$\frac{\partial \theta}{\partial t} = \beta w + \kappa \nabla^2 \theta \tag{12}$$

where $\nabla^2 = \frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial y^2} + \frac{\partial^2}{\partial z^2}$ and; $\zeta = \frac{\partial v}{\partial x} - \frac{\partial u}{\partial y}$ denote the z-component of vorticity.

NORMAL MODE ANALYSIS

Analyzing the disturbances into normal modes, we assume that the Perturbation quantities are of the form

Research Article

$$[w,\theta,\varsigma] = [W(z),\Theta(z),Z(z)]\exp(ik_x x + ik_y y + nt),$$
(13)

Where k_x, k_y are the wave numbers along the x- and y-directions, respectively, $k = (k_x^2 + k_y^2)^{\frac{1}{2}}$, is the resultant wave number, and n is the growth rate which is, in general, a complex constant. Using (13), equations (10) – (12), in non-dimensional form transform to

$$(D^{2} - a^{2})(1 + F\sigma)(D^{2} - a^{2}) - \sigma]W = Ra^{2}\Theta + T_{A}DZ,$$

$$[(1 + F\sigma)(D^{2} - a^{2}) - \sigma]Z = -DW,$$
(14)
(15)

$$(D^2 - a^2 - p_1 \sigma)\Theta = -W, \qquad (16)$$

Where we have introduced new coordinates (x', y', z') = (x/d, y/d, z/d) in new units of length d and D = d/dz'. For convenience, the dashes are dropped hereafter. Also we have substituted $a = kd, \sigma = \frac{nd^2}{v}, p_1 = \frac{v}{\kappa}$, is the thermal Prandtl number; $p_2 = \frac{v}{\eta}$, is the magnetic Prandtl equation $dz = \frac{v}{\eta}$.

number; $F = \frac{v}{d^2}$, is the Rilvin-Ericksen kinematic viscoelasticity parameter; $R = \frac{g\alpha\beta d^4}{\kappa v}$, is the

thermal Rayleigh number and $T_A = \frac{4\Omega^2 d^4}{v^2}$, is the Taylor number. Also we have Substituted $W = W_{\oplus}$,

$$\Theta = \frac{\beta d^2}{\kappa} \Theta_{\oplus}, \ Z = \frac{2\Omega d}{v} Z_{\oplus}, \ \text{and} \ D_{\oplus} = dD \text{, and dropped } (\oplus) \text{ for convenience.}$$

We now consider the case where both the boundaries are rigid and perfectly conducting and are maintained at constant temperature, then the perturbations in the temperature are zero at the boundaries. The appropriate boundary conditions with respect to which equations (14)-(16), must possess a solution are

$$W = DW = 0$$
, $\Theta = 0$ and $Z=0$ at $z = 0$ and $z = 1$. (17)

Equations (14)-(16), along with boundary conditions (17), pose an eigenvalue problem for σ and we wish to characterize σ_i when $\sigma_r \ge 0$.

We first note that since W and Z satisfy W(0) = 0 = W(1) and Z(0) = 0 = Z(1) in addition to satisfying to governing equations and hence we have from the Rayleigh-Ritz inequality (1973)

$$\int_{0}^{1} |DW|^{2} dz \ge \pi^{2} \int_{0}^{1} |W|^{2} dz , \qquad (18)$$

and

$$\int_{0}^{1} |DZ|^{2} dz \ge \pi^{2} \int_{0}^{1} |Z|^{2} dz, \qquad (19)$$

Further, for W(0) = 0 = W(1) and Z(0) = 0 = Z(1), Banerjee et al (1992) have show that

$$\int_{0}^{1} \left| D^{2}W \right|^{2} dz \ge \pi^{2} \int_{0}^{1} \left| DW \right|^{2} dz \text{ And } \int_{0}^{1} \left| D^{2}Z \right|^{2} dz \ge \pi^{2} \int_{0}^{1} \left| DZ \right|^{2} dz , \qquad (20)$$

MATHEMATICAL ANALYSIS

We prove the following lemma:

Lemma 1: For any arbitrary oscillatory perturbation, neutral or unstable

Research Article

$$\int_{0}^{1} |Z|^{2} dz \langle \frac{1}{\pi^{4}} \int_{0}^{1} |DW|^{2} dz \text{ And } \int_{0}^{1} \left\{ |DZ|^{2} + a^{2} |Z|^{2} \right\} dz \langle \frac{1}{\pi^{2}} \int_{0}^{1} |DW|^{2} dz.$$

Proof: Further, multiplying equation (15) with its complex conjugate, and integrating by parts each term on both sides of the resulting equation for an appropriate number of times and making use of boundary condition on Z namely Z(0) = 0 = Z(1) along with (17), we get

$$(1 + 2F\sigma_{r} + F^{2}|\sigma|^{2})\int_{0}^{1} \left\{ D^{2}Z \right|^{2} + 2a^{2}|DZ|^{2} + a^{4}|Z|^{2} \right\} dz + (2\sigma_{r} + 2F|\sigma|^{2})\int_{0}^{1} \left\{ DZ \right|^{2} + a^{2}|Z|^{2} \right\} dz + |\sigma|^{2} \int_{0}^{1} |Z|^{2} dz = \int_{0}^{1} |DW|^{2} dz, \qquad (21)$$

And on utilizing the inequalities (19) and (20), equation (21) gives

$$\int_{0}^{1} |Z|^{2} dz \langle \frac{1}{\pi^{4}} \int_{0}^{1} |DW|^{2} dz \text{ and } \int_{0}^{1} \left\{ |DZ|^{2} + a^{2} |Z|^{2} \right\} dz \langle \frac{1}{\pi^{2}} \int_{0}^{1} |DW|^{2} dz , \qquad (22)$$

We prove the following theorem:

Theorem 1: If $\mathbb{R} \ 0$, $\mathbb{F} \ 0$, $T_A \ 0$, $\sigma_r \ge 0$ and $\sigma_i \ne 0$ then the necessary condition for the existence of non-trivial solution (W, Θ, Z) of equations (16), (17) and (18) together with boundary conditions (19) is that

$$\frac{T_A(1+\pi^2 F)}{\pi^4}\rangle 1.$$

Proof: Multiplying equation (14) by W^* (the complex conjugate of W) throughout and integrating the resulting equation over the vertical range of z, we get

$$(1+F\sigma)\int_{0}^{1}W^{*}(D^{2}-a^{2})^{2}Wdz - \sigma\int_{0}^{1}W^{*}(D^{2}-a^{2})Wdz = Ra^{2}\int_{0}^{1}W^{*}\Theta dz + T_{A}\int_{0}^{1}W^{*}DZdz, \qquad (23)$$

Taking complex conjugate on both sides of equation (16), we get $(D^2 - a^2 - p_1 \sigma^*) \Theta^* = -W^*$, (24) Therefore, using (24), we get

$$\int_{0}^{1} W^{*} \Theta dz = -\int_{0}^{1} \Theta \left(D^{2} - a^{2} - p_{1} \sigma^{*} \right) \Theta^{*} dz , \qquad (25)$$

Also taking complex conjugate on both sides of equation (15), we get $[(1 + F\sigma^*)(D^2 - a^2) - \sigma^*]Z^* = -DW^*$,

Therefore, using (26) and appropriate boundary condition (17), we get

$$\int_{0}^{1} W^* DZ dz = -\int_{0}^{1} DW^* Z dz = \int_{0}^{1} Z \{ (1 + F\sigma^*) (D^2 - a^2) - \sigma^* \} Z^* dz , \qquad (27)$$

Substituting (25) and (27) in the right hand side of equation (23), we get

$$(1+F\sigma)\int_{0}^{1}W^{*}(D^{2}-a^{2})^{2}Wdz - \sigma\int_{0}^{1}W^{*}(D^{2}-a^{2})Wdz$$

= $-Ra^{2}\int_{0}^{1}\Theta(D^{2}-a^{2}-p_{1}\sigma^{*})\Theta^{*}dz + T_{A}\int_{0}^{1}Z\{(1+F\sigma^{*})(D^{2}-a^{2})-\sigma^{*}\}Z^{*}dz,$ (28)

(26)

Research Article

Integrating the terms on both sides of equation (25) for an appropriate number of times by making use of the appropriate boundary conditions (19), along with (17), we get

$$(1+F\sigma)\int_{0}^{1} \left\{ D^{2}W \right\}^{2} + 2a^{2} |DW|^{2} + a^{4} |W|^{2} dz + \sigma \int_{0}^{1} \left\{ DW \right\}^{2} + a^{2} |W|^{2} dz$$
$$= Ra^{2} \int_{0}^{1} \left\{ D\Theta \right\}^{2} + a^{2} |\Theta|^{2} + p_{1}\sigma^{*} |\Theta|^{2} dz - T_{A}(1+F\sigma^{*}) \int_{0}^{1} \left\{ DZ \right\}^{2} + a^{2} |Z|^{2} dz - T_{A}\sigma^{*} \int_{0}^{1} |Z|^{2} dz, \qquad (29)$$

And equating imaginary parts on both sides of equation (29), and cancelling $\sigma_{i} \neq 0$ throughout, we get

$$F\int_{0}^{1} \left\{ D^{2}W \right|^{2} + 2a^{2} |DW|^{2} + a^{4} |W|^{2} dz + \int_{0}^{1} \left\{ DW \right|^{2} + a^{2} |W|^{2} dz$$

= $-Ra^{2} p_{1} \int_{0}^{1} |\Theta|^{2} dz + T_{A} F \int_{0}^{1} \left\{ DZ \right|^{2} + a^{2} |Z|^{2} dz + T_{A} \int_{0}^{1} |Z|^{2} dz ,$ (30)

Now R \rangle 0, F \rangle 0 and $T_A \rangle$ 0, utilizing the inequalities (19, (20) and (22), the equation (30) gives,

$$\left[(1 - \frac{T_A}{\pi^4} (1 + \pi^2 F)) \right]_0^1 |DW|^2 dz + I_1 \langle 0,$$
(31)
Where

where

$$I_{1} = F \int_{0}^{1} \left\{ D^{2}W \right|^{2} + 2a^{2} |DW|^{2} + a^{4} |W|^{2} \right\} dz + a^{2} \int_{0}^{1} \left\{ W \right\|^{2} dz + Ra^{2} p_{1} \int_{0}^{1} |\Theta|^{2} dz ,$$

Is positive definite.

and therefore, we must have

$$\frac{\Gamma_A(1+\pi^2 F)}{\pi^4} \rangle 1.$$
(39)

Hence, if

$$\sigma_r \ge 0 \text{ And } \sigma_i \ne 0$$
, then $\frac{T_A(1 + \pi^2 F)}{\pi^4} > 1$

And this completes the proof of the theorem.

Presented otherwise from the point of view of existence of instability as stationary convection, the above theorem can be put in the form as follow:-

Theorem 2: The sufficient condition for the validity of the 'exchange principle' and the onset of instability as a non-oscillatory motions of non-growing amplitude in a Rivlin-Ericksen viscoelastic fluid

heated from below, in the presence of uniform vertical rotation is that $\frac{T_A(1 + \pi^2 F)}{\pi^4} \le 1$, where T_A is the

Taylor number and F is the viscoelasticity parameter, for horizontal rigid boundaries of infinite extension at the top and bottom of the fluid.

or

The onset of instability in a Rivlin-Ericksen viscoelastic fluid heated from below, in the presence of uniform vertical rotation, cannot manifest itself as oscillatory motions of growing amplitude, if the Taylor

number T_A and the viscoelasticity parameter F, satisfy the inequality, $\frac{T_A(1+\pi^2 F)}{\pi^4} \le 1$, for horizontal

rigid boundaries of infinite extension at the top and bottom of the fluid. *Special Case*: When the viscoelasticity parameter F = 0, then

Research Article

$$\frac{T_A}{\pi^4} \le 1 \,,$$

and then the Rivlin-Ericksen viscoelastic fluid behaves like an ordinary Newtonian fluid and we retrieve the result of (Gupta et al (1986)).

In the context of existence of instability in 'oscillatory modes' and that of 'overstability in the present configuration, we can state the above theorem as follow:-

Theorem 3: The necessary condition for the existence of instability in 'oscillatory modes' and that of 'overstability' in a Rivlin-Ericksen viscoelastic fluid heated from below, in the presence of uniform vertical rotation, is that the Taylor number T_A and the viscoelasticity parameter F must satisfy the

inequality $\frac{T_A(1+\pi^2 F)}{\pi^4}$ $\rangle 1$, for horizontal rigid boundaries of infinite extension at the top and bottom of

the fluid.

CONCLUSIONS

This theorem mathematically established that the onset of instability in a Rivlin-Ericksen viscoelastic fluid in the presence of uniform vertical rotation cannot manifest itself as oscillatory motions of growing amplitude if the Taylor number T_A and the viscoelasticity parameter F, satisfy the T_A (1 + $-2T_A$)

inequality $\frac{T_A(1 + \pi^2 F)}{\pi^4} \le 1$, for horizontal rigid boundaries of infinite extension at the top and bottom of

the fluid.

The essential content of the theorem, from the point of view of linear stability theory is that for the configuration of Rivlin-Ericksen viscoelastic fluid of infinite horizontal extension heated form below, having rigid boundaries at the top and bottom of the fluid, in the presence of uniform vertical rotation parallel to the force field of gravity, an arbitrary neutral or unstable modes of the system are definitely

non-oscillatory in character if $\frac{T_A(1 + \pi^2 F)}{\pi^4} \le 1$, and in particular PES is valid.

REFERENCES

Banerjee MB, Katoch DC, Dube GS and Banerjee K (1981). Bounds for growth rate of perturbation in thermohaline convection. *Proceeding of the Royal Society A* 378 301-304.

Banerjee MB and Banerjee B (1984). A characterization of non-oscillatory motions in magnetohydronamics. *Indian Journal of Pure and Applied Mathematics* **15**(4) 377-382.

Banerjee MB, Gupta, JR and Prakash, J (1992). On thermohaline convection of Veronis type, *Journal of Mathematical Analysis and Applications* 179 327-334.

Banyal AS (2011). The necessary condition for the onset of stationary convection in couple-stress fluid, *IJournal of Fluid Mechanics and Research*, **38**(5) 450-457.

Bénard H (1900). Les tourbillions cellulaires dans une nappe liquid, Revue Genérale des Sciences Pures et Appliquees 11, 1261-1271, 1309-1328.

Bhatia PK and Steiner JM (1972). Convective instability in a rotating viscoelastic fluid layer, Zeitschrift fur Angewandte Mathematik and Mechanik , **52** 321-327.

Bhatia PK and Steiner JM (1973). Thermal Instability in a viscoelastic fluid layer in hydromagnetics, *Journal of Mathematical Analysis and Applications* **41**(2) 271-283.

Chandrasekhar, S, Hydrodynamic and Hydromagnetic Stability (1981), Dover Publication, New York.

Research Article

Rivlin, RS and Ericksen, JL (1955). Stress deformation relations for isotropic materials, *Journal of Rat Mechanics and Analysis* **4** 323-429

Gupta JR, Sood SK and Bhardwaj UD (1986). On the characterization of nonoscillatory motions in rotatory hydromagnetic thermohaline convection, *Indian Journal of pure applied Mathematics*, 17(1) 100-107.

Jeffreys H (1926). The stability of a fluid layer heated from below, Philosophical Magazine 2 833-844.

Kumar P, Mohan H and Lal R (2006). Effect of magnetic field on thermal instability of a rotating Rivlin-Ericksen viscoelastic fluid, *International Journal of Mathematics and Mathematical Sciences*, article ID 28042, 1-10.

Oldroyd JG (1958). Non-Newtonian effects in steady motion of some idealized elastic-viscous liquids, *Proceedings of the Royal Society of London* A245, 278-297.

Pellow A and Southwell RV (1940). On the maintained convective motion in a fluid heated from below, *Proceeding of the Royal Society London* A, **176** 312-43.

Rayleigh L (1916). On convective currents in a horizontal layer of fluid when the higher temperature is on the underside, *Philosophical Magazine* **32** 529-546.

Schultz MH (1973). Spline Analysis, Prentice Hall, Englewood Cliffs, New Jersy.

Sharma RC (1976). Effect of rotation on thermal instability of a viscoelastic fluid, Acta Physica Hungarica 40 11-17.

Sharma RC (1975). Thermal instability in a viscoelastic fluid in hydromagnetics, Acta Physica Hungarica, 38 293-298.

Sharma RC and Kumar P (1996). Effect of rotation on thermal instability in Rivlin-Ericksen elastic-viscous fluid, Zeitschrift fur Naturforschung 51a, 821-824.